



## General Characteristics

|                                     |          |
|-------------------------------------|----------|
| Rated Power (kW/kVA)                | 2.80/2.8 |
| Maximum Power (kW/kVA)              | 4.00/4   |
| Rated Current (A)                   | 12.17    |
| Voltage (V)                         | 230      |
| Phase Count                         | 1        |
| Power Factor                        | 1        |
| Frequency (Hz)                      | 50       |
| Cycle (rpm)                         | 1500     |
| Fuel Tank Capacity (l)              | 81       |
| Fuel Consumption at Full Load (l/h) | 1.01     |
| Auxiliary Socket                    | x2       |

## Tower Properties

|                 |          |
|-----------------|----------|
| Mast Height (m) | 8        |
| Number of Lamp  | 4        |
| Lamp Power (W)  | 400      |
| Lamp Type       | Flat Led |

## Size And Weight (With Trailer)

|                                |      |
|--------------------------------|------|
| Width (mm)                     | 1280 |
| NumHeight2erofLamp             | 2965 |
| Altitude (mm)                  | 1880 |
| Telescopic Legs Open Wide (mm) | 2290 |

## Standard Properties

info@aksa.ly

091-3178688

091-2198688



الفرع الرئيسي - تاجوراء - البيفي - بجانب تريبولي مول



بنغازي - طريق المطار



- Maximum 8 meters
- 360° manual
- Super silent (62dB at 7m)
- Maximum speed 80km/h
- Single Phase
- 50 Hz Frequency
- 1500 R.P.M
- Water-cooled system
- LED light (available to start and stop at any time)
- Diesel fuel
- Emergency stop
- External fuel refilling
- 4 stabilizers, two of which are extensible to ensure stability
- Spirit level located at the top of genset
- Huge space for maintenance and control
- Power socket provided
- Extensible and tilting mast
- Draw bar with ball coupling
- Includes lifting hooks and bracket holders
- Cabinet with electrophoresis and powder coating process

